



Design Example Report

Title	22 W Triple Output Flyback Converter using DPA424R
Specification	Input: 28 – 60 VDC Output: 3.3 V / 2 A, 9 V / 0.6 A, 24 V / 0.4 A
Application	Security Camera
Author	Power Integrations Applications Department
Document Number	DER-120
Date	October 26, 2005
Revision	1.0

Summary and Features

- Low parts Count
- High-Efficiency ~80% 48 VDC Input and Full Load
- Good cross-regulation

The products and applications illustrated herein (including circuits external to the products and transformer construction) may be covered by one or more U.S. and foreign patents or potentially by pending U.S. and foreign patent applications assigned to Power Integrations. A complete list of Power Integrations' patents may be found at www.powerint.com.

Table Of Contents

1	Introduction	4
2	Power Supply Specification	5
3	Schematic	6
4	Circuit Description.....	7
4.1	Input EMI filtering.....	7
4.2	Output Rectification	7
4.3	Output Feedback	7
5	PCB Layout.....	8
6	Bill Of Materials.....	9
6.1	Triple Output Flyback Converter.....	9
7	Transformer Specification	10
7.1	Electrical Specifications	10
7.2	Materials	10
7.3	Transformer Build Diagram.....	11
7.4	Transformer Construction	11
8	Transformer Spreadsheets	12
9	Performance Data.....	13
9.1	Cross Regulation Matrix	13
9.2	Regulation	14
9.2.1	LINE	14
9.2.2	LOAD.....	15
10	Waveforms	16
10.1	Drain Voltage, Normal Operation.....	16
10.2	Output Voltage Start-up Profile.....	17
10.3	Load Transient Response (0.75 A to 2 A Load Step)	18
10.4	Output Ripple Measurements	19
10.4.1	Ripple Measurement Technique.....	19
10.4.2	Measurement Results at 48 VDC	20
11	Control Loop Measurements	21
11.1	Maximum Load	21
11.2	Minimum Load	22
12	Revision History	24



List Of Figures

Figure 1 – Populated Circuit Board (Top-side).....	4
Figure 2 – Schematic	6
Figure 3 – Printed Circuit Layout.....	8
Figure 4 – Transformer Diagram.....	10
Figure 5 – Transformer Cross-Section	11
Figure 6 – Line Regulation, Full Load	14
Figure 7 – Load Regulation, 28 V and 60 VDC Input.....	15
Figure 8 – 48 VDC, No Load.....	16
Figure 9 – 48 VDC Input, Full Load.....	16
Figure 10 – 48 VDC, Minimum Load.....	16
Figure 11 – 60 VDC Input, Full Load.....	16
Figure 12 – Start-up Profile, 48 VDC No Load T: 10msec/div.....	17
Figure 13 – Start-up Profile, 48 VDC Full Load T: 10msec/div	17
Figure 14 – Transient Response Top: Load Current; 1 A/div. Bottom: +3.3 V Output 100 mV, 1ms/div.	18
Figure 15 – Oscilloscope Probe Prepared for Ripple Measurement. (End Cap and Ground Lead Removed)	19
Figure 16 – Oscilloscope Probe with Probe Master 5125BA BNC Adapter. (Modified with wires for probe ground for ripple measurement, and two parallel decoupling capacitors added)..	19
Figure 17 – +3.3 V Ripple, Full Load, 20mV/div; T: 2usec/div	20
Figure 18 – +9 V Ripple, Full Load, 50mV/div; T: 2usec/div	20
Figure 19 – +24 V Ripple, Full Load, 50mV/div; T: 2usec/div	20
Figure 20 – Gain-Phase Plot, 28VDC Input Maximum Steady State Load Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div. Crossover Frequency = 4.55 kHz Phase Margin = 49.4°	21
Figure 21 – Gain-Phase Plot, 48VDC Input Maximum Steady State Load Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div. Crossover Frequency = 2.23 kHz Phase Margin = 63.7°	21
Figure 22 – Gain-Phase Plot, 60 VDC Input Maximum Steady State Load Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div. Crossover Frequency = 2.27 kHz Phase Margin = 76.7°	22
Figure 23 – Gain-Phase Plot, 28 VDC Input Minimum Load Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div. Crossover Frequency = 4.97 kHz Phase Margin = 74.8°	22
Figure 24 – Gain-Phase Plot, 48 VDC Input Minimum Load Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div. Crossover Frequency = 1.28 kHz Phase Margin = 76.1°	23
Figure 25 – Gain-Phase Plot, 60 VDC Input Minimum Load Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div. Crossover Frequency = 896Hz Phase Margin = 53.98°	23

Important Note:

This board is designed to be non-isolated. However the outputs are high voltage so please take the necessary safety precautions.

Design Reports contain a power supply design specification, schematic, bill of materials, and transformer documentation. Performance data and typical operation characteristics are included. Typically only a single prototype has been built.



1 Introduction

This document is an engineering report describing a triple output Flyback converter employing the DPA424R. The input voltage range is 28 to 60 VDC providing a regulated +3.3 V at 2 A and a cross-regulated +9 V @ 0.6 A and +24 V @ 0.4 A.

This document contains the power supply specification, schematic, and bill of materials, transformer documentation, printed circuit layout, and performance data.




Figure 1 – Populated Circuit Board (Top-side).



2 Power Supply Specification

Description	Symbol	Min	Typ	Max	Units	Comment
Input						
Voltage No-load Input Power (60V _{DC})	V_{IN}	28	48	60 1.2	V _{DC} W	
Output						
Output Voltage 1	V_{OUT1}	3.135	3.3	3.465	V	$\pm 5\%$
Output Ripple Voltage 1	$V_{RIPPLE1}$			50	mV	20 MHz Bandwidth
Output Current 1	I_{OUT1}	0.75		2	A	
Output Voltage 2	V_{OUT2}	8.10	9.0	9.90	V	$\pm 10\%$
Output Ripple Voltage 2	$V_{RIPPLE2}$			200	mV	20 MHz Bandwidth
Output Current 2	I_{OUT2}	0.3		0.6	A	
Output Voltage 3	V_{OUT3}	21.6	24.0	26.4	V	$\pm 10\%$
Output Ripple Voltage 3	$V_{RIPPLE3}$			300	mV	20 MHz Bandwidth
Output Current 3	I_{OUT3}	0.1		0.4	A	
Total Output Power						
Continuous Output Power	P_{OUT}	7.6		21.6	W	
Peak Output Power	P_{OUT_PEAK}				W	
Efficiency	η		80		%	Measured at Max. P _{OUT} , 25 °C
Ambient Temperature	T_{AMB}	0		40	°C	Free convection, Sea level

3 Schematic




Figure 2 – Schematic.



4 Circuit Description

4.1 Input EMI filtering

Figure 1 shows a single-ended Flyback converter using the DPA424R. The circuit is designed for an input range of 28 V to 60 V providing three isolated outputs at +3.3 V, +9 V and +24 V at 2 A, 0.6 A and 0.4 A respectively. C10 and C14 bypass the DC rail. The DC rail is applied to the primary winding of T1. The other side of the transformer primary is driven by the integrated MOSFET in U1. VR1 clamps the U1 drain leakage spikes. C1 and R3 dampen the drain-source voltage ringing.

R9 is used to set the low line turn-on threshold to approximately 23 V, and also sets the over-voltage shutdown level to approximately 61 V. C4 bypasses the U1 control pin, and provides the peak current necessary for driving the **DPA-Switch** internal MOSFET. C5 has three functions. It provides the energy required by U1 during startup, sets the auto-restart frequency during fault conditions, and also reduces the gain of U1 as a function of frequency. R1 adds a zero to stabilize the power supply control loop.

4.2 Output Rectification

The output of T1 is rectified and filtered by D3 (D7, D2) and C2 (C6, C12). L6 and C8 provide additional high frequency filtering.

An auxiliary Flyback winding on T1 powers U1 during normal operation. This winding delivers energy during the off time of U1, with an output voltage proportional to the supply output voltage. The turns-ratio of T1 sets the output voltage of the auxiliary winding to approximately 12 V. D4 and C8 rectify and filter the auxiliary winding output.

4.3 Output Feedback

R6 and R7 divide down the supply output voltage and apply it to the reference pin of error amplifier U3. C9 and R8 roll off the gain of U3. U3 drives the opto-coupler LED of U2 through resistor R10 to provide feedback information to the CONTROL pin of U1. The opto-coupler phototransistor output also provides power to U1 during normal operating conditions. R2 provides bias current to U3.

5 PCB Layout




Figure 3 – Printed Circuit Layout.

6 Bill Of Materials

6.1 Triple Output Flyback Converter

Item	Qty	Ref	Description	P/N	Manufacturer
1	1	C1	390pF/200V	C1210C391K2GAC	Kemet
2	1	C2	100uF/10V/Polymer	EEUFUD0J101RX	Panasonic
3	1	C3	4.7uF/16V	ECST1CY475R	Panasonic
4	1	C4	0.47uF/0805		
5	1	C5	68uF/16V	ECST1CD686R	Panasonic
6	1	C6	100uF/16V	T494D107(1)016AS	Kemet
7	1	C7	1nF/1kV/1812	18122R102KEBB0D	Yageo
8	1	C8	4.7uF/10V	ECST1AY475R	Panasonic
9	1	C9	1uF/0805		
10	1	C10	1uF/100V	C4532X7R2A105M	TDK
11	1	C12	4.7uF/10V	C3216X5R1A475K	TDK
12	1	C14	1uF/100V	C4532X7R2A105M	TDK
13	1	D1	160V TVS	P6SMB160A/SMB	On Semiconductor
14	1	D2	1A/80V Schottky	B180/SMB	Diodes, Inc
15	1	D3	5A/20V Schottky	B520/SMC	Diodes, Inc
16	1	D4	Small Signal Diode	SD101AW/SOD323	Diodes, Inc
17	1	D7	1A/40V Schottky	B140/SMB	Diodes, Inc
18	1	L6	1uH		
19	1	R1	1/0603		
20	1	R2	1k/0805		
21	1	R3	680 1/4W		
22	1	R5	10R/0805		
23	1	R6	27.4k/1%/0603		
24	1	R7	86.6k/1%/0603		
25	1	R8	220/0603		
26	1	R9	453k/0805		
27	1	R10	68/0805		
28	1	T1	Custom Flyback EFD20		
29	1	U1	PWM + MOSFET	DPA424R	Power Integrations
30	1	U2	Opto-coupler	PC317A	Sharp
31	1	U3	Prec. Shunt Regulator	LM431A/SOT23	National Semiconductor

7 Transformer Specification




Figure 4 – Transformer Diagram

7.1 Electrical Specifications

Electrical Strength	1 second, from Pins 1-5 to Pins 6-10	1000 VDC
Creepage	Between Pins 1-5 and Pins 6-10	N/A
Primary Inductance	Pins 1,2, all other windings open, measured at 400KHz, 400mVRMS	40 μ H, $\pm 10\%$
Resonant Frequency	Pins 1,2, all other windings open	5.0 MHz (Min.)
Primary Leakage Inductance	Pins 1,2, with Pins 6-10 shorted, measured at 400KHz, 400mVRMS	0.75 μ H (Max.)

7.2 Materials

Item	Description
[1]	Core: EFD20/3F3 or equivalent gap for A_L of 133 nH/T ²
[2]	Bobbin: 10 pin surface mount
[3]	Magnet Wire: #32 AWG Double Coated
[4]	Foil
[5]	Tape, Polyester
[6]	Varnish



7.3 Transformer Build Diagram




Figure 5 – Transformer Cross-Section

7.4 Transformer Construction

Primary	Start at Pin 2. Wind 17 trifilar turns of item [3] uniformly on a single layer. Finish on pin 1.
Basic Insulation	Use one layer of item [5] for basic insulation.
Bias Winding	Start at Pin 5. Wind 6 turns of 9 strands of item [3] uniformly on a single layer. Finish on Pin 4.
Insulation	Use 3 layers of item [5] for basic insulation.
+3.3 V Winding	Prepare cuffed foil assembly. Start at Pin 10. Wind 2 turns of item [4]. Finish on pin 7 and 9.
Basic Insulation	Use one layer of item [5] for basic insulation.
+9 V & +12 V Windings	Wind +9 V and +12 V windings simultaneously and uniformly on a single layer. Start +9 V winding on pin 8 with 7 strands on item [3] and start +12 V winding on pin 6 with a quadfilar item [3] make 3 turns and finish +9V windings to pin 10. Continue +12 v windings an additional 5 turns and finish on pin 8.
Outer Wrap	Wrap windings with 3 layers of tape [item [5]].
Final Assembly	Assemble and secure core halves. Dip varnish cores (item [6]). Do not impregnate

8 Transformer Spreadsheets

A	B	D	F	G	I
DPAswitch_Flyback_Rev_1e_090302: Copyright Power Integrations Inc. 2002	INPUT	INFO	OUTPUT	UNITS	DPAswitch_Flyback_090302 - Continuous/Discontinuous mode Spreadsheet. Copyright 2002 Power Integrations
ENTER APPLICATION VARIABLES					
..... h DPA					
VDCMIN	28		Volts		Minimum DC Input Voltage
VDCMAX	60		Volts		Maximum DC Input Voltage
VO	3.3		Volts		Output Voltage
PO	22		Watts		Output Power
n	0.86				Efficiency Estimate
Z			0.7		Loss Allocation Factor, (0.7 Recommended)
VB	15		Volts		Bias Voltage
UV AND OV PARAMETERS					
		min	max		
VUVOFF	22.8	25.1	Volts		Minimum undervoltage On-Off threshold
VUVON	24.4	26.2	Volts		Maximum undervoltage Off-On threshold (turn-on)
VOVON	55.9	-	Volts		Minimum overvoltage Off-On threshold
VOVOFF		70.5	Volts		Maximum overvoltage On-Off threshold (turn-off)
RL		456.6	k-Ohms		Line Sense Resistor
ENTER DPASWITCH VARIABLES					
DPASWITCH	dpa424		16VDC		
Chosen Device	DPA424		Power Out	15.5W	36VDC 35W
ILIMITMAX	2.32	2.68	Amps		From DPASWITCH Data Sheet
Frequency	f				Enter "f" for fS = 400kHz and "L" for fS = 300KHz
fS	400000		Hertz		DPASWITCH Switching Frequency
VOR	33	33	Volts		Reflected Output Voltage
KI	1.00	1			Current Limit Reduction Factor
ILIMITTEXT		2.320	Amps		Minimum External Current limit
RX		-	k-Ohms		Resistor from X pin to source to set external current limit
VDS	2.5		Volts		DPASWITCH on-state Drain to Source Voltage
VD	0.5		Volts		Output Winding Diode Forward Voltage Drop
VDB	0.7		Volts		Bias Winding Diode Forward Voltage Drop
KRP/KDP	0.45				Ripple to Peak Current Ratio (0.2 < KRP < 1.0 : 1.0 < KDP < 6.0)
ENTER TRANSFORMER CORE/CONSTRUCTION VARIABLES					
Core Type	efd20		P/N:		
Core Manuf					
Bobbin Manuf					
Core	EFD20		P/N:		EFD20-3F3-Exxx-xx
Bobbin	EFD20 Bobbin		P/N:	0	
AE		0.31	cm ²		Core Effective Cross Sectional Area
LE		4.7	cm		Core Effective Path Length
AL		1200	nH/T ²		Unapped Core Effective Inductance
BW		13.5	mm		Bobbin Physical Winding Width
M	0		mm		Safety Margin Width (Half the Primary to Secondary Creepage Distance)
L	1				Number of Primary Layers
NS	2				Number of Secondary Turns
CURRENT WAVEFORM SHAPE PARAMETERS					
DMAX		0.56			Maximum Duty Cycle
IAVG		0.91	Amps		Average Primary Current
IP	Warning	2.09	Amps		!!!!!! REDUCE Ip < KI*0.9*2.32 (increase VOR, decrease KDP/larger DPASWITCH)
IR		0.94	Amps		Primary Ripple Current
IRMS		1.23	Amps		Primary RMS Current
TRANSFORMER PRIMARY DESIGN PARAMETERS					
LP		40	uHenries		Primary Inductance
NP		17			Primary Winding Number of Turns
NB		8			Bias Winding Number of Turns
ALG		133	nH/T ²		Gapped Core Effective Inductance
BP	Warning	1733	Gauss		Peak Flux density during transients (Limit to 4000 Gauss)
BM		1561	Gauss		Peak Flux density<2000 Gauss, A smaller core may be used
BAC		351	Gauss		AC Flux Density for Core Loss Curves (0.5 X Peak to Peak)
ur		1448			Relative Permeability of Ungapped Core
LG		0.26	mm		Gap Length (Lg >> 0.051 mm)
BWE		13.5	mm		Effective Bobbin Width
TRANSFORMER SECONDARY DESIGN PARAMETERS					
ISP		18.15	Amps		Peak Secondary Current
ISRMS		9.42	Amps		Secondary RMS Current
IO		6.67	Amps		Power Supply Output Current
IRIPPLE		6.65	Amps		Output Capacitor RMS Ripple Current
VOLTAGE STRESS PARAMETERS					
VDRAIN		149	Volts		Maximum Drain Voltage (Includes Effect of Leakage Inductance)
PIVS		10	Volts		Output Rectifier Maximum Peak Inverse Voltage
PIVB		44	Volts		Bias Rectifier Maximum Peak Inverse Voltage
ADDITIONAL OUTPUTS					
V_OUT2	9.0000		Volts		Auxiliary Output Voltage
VD_OUT2	0.5000		Volts		Auxiliary Diode Forward Voltage Drop
N_OUT2		5.00			Auxiliary Number of Turns
PIV_OUT2		26	Volts		Auxiliary Rectifier Maximum Peak Inverse Voltage
V_OUT3	24		Volts		Auxiliary Output Voltage
VD_OUT3	0.75		Volts		Auxiliary Diode Forward Voltage Drop
N_OUT3		13.03			Auxiliary Number of Turns



9 Performance Data

All measurements performed at room temperature.

9.1 Cross Regulation Matrix

Input Voltage 28

		LOAD	Regulation		LOAD	Regulation		LOAD	Regulation	
<i>+3.3V</i>	3.39	0	102.7%	3.34	0.75	101.2%	3.35	0.75	101.5%	
	9.35	0	103.9%		9.1	0.3	101.1%	9.06	0.3	100.7%
	24.32	0	101.3%		24.22	0.1	100.9%	23.83	0.4	99.3%
<i>Input Current</i>	0.018		η	0.353		η	0.667		η	
	0.504		0.000%		9.884	77.469%		18.676		
<i>+3.3V</i>	3.35	0.75	101.5%	3.35	0.75	101.5%	3.33	2	100.9%	
	8.94	0.6	99.3%		8.89	0.6	98.8%	9.7	0.3	107.8%
	24.14	0.1	100.6%		23.74	0.4	98.9%	25.89	0.1	107.9%
<i>Input Current</i>	0.466		η	0.791		η	0.571		η	
	13.048		78.866%		22.148	78.303%		15.988		
<i>+3.3V</i>	3.35	2	101.5%	3.33	2	100.9%	3.34	2	101.2%	
	9.66	0.3	107.3%		9.51	0.6	105.7%	9.48	0.6	105.3%
	25.44	0.4	106.0%		25.81	0.1	107.5%	25.36	0.4	105.7%
<i>Input Current</i>	0.929		η	0.695		η	1.067		η	
	26.012		76.019%		19.46	76.809%		29.876		

Input Voltage 48

		LOAD	Regulation		LOAD	Regulation		LOAD	Regulation	
<i>+3.3V</i>	3.43	0	103.9%	3.38	0.75	102.4%	3.37	0.75	102.1%	
	10.05	0	111.7%		9.11	0.3	101.2%	9.01	0.3	100.1%
	26.16	0	109.0%		24.18	0.1	100.8%	23.52	0.4	98.0%
<i>Input Current</i>	0.019		η	0.215		η	0.391		η	
	0.912		0.000%		10.32	74.477%		18.768		
<i>+3.3V</i>	3.37	0.75	102.1%	3.37	0.75	102.1%	3.35	2	101.5%	
	8.93	0.6	99.2%		8.82	0.6	98.0%	9.48	0.3	105.3%
	24.01	0.1	100.0%		23.45	0.4	97.7%	25.27	0.1	105.3%
<i>Input Current</i>	0.277		η	0.452		η	0.333		η	
	13.296		77.365%		21.696	79.275%		15.984		
<i>+3.3V</i>	3.36	2	101.8%	3.36	2	101.8%	3.36	2	101.8%	
	9.4	0.3	104.4%		9.32	0.6	103.6%	9.29	0.6	103.2%
	24.7	0.4	102.9%		25.16	0.1	104.8%	24.67	0.4	102.8%
<i>Input Current</i>	0.514		η	0.397		η	0.581		η	
	24.672		78.713%		19.056	77.813%		27.888		

Input Voltage 60

		LOAD	Regulation		LOAD	Regulation		LOAD	Regulation	
<i>+3.3V</i>	3.4	0	103.0%	3.36	0.75	101.8%	3.37	0.75	102.1%	
	10.13	0	112.6%		9.09	0.3	101.0%	9.02	0.3	100.2%
	26.27	0	109.5%		24.17	0.1	100.7%	23.7	0.4	98.8%
<i>Input Current</i>	0.018		η	0.167		η	0.3		η	
	1.08		0.000%		10.02	76.487%		18		
<i>+3.3V</i>	3.36	0.75	101.8%	3.36	0.75	101.8%	3.35	2	101.5%	
	8.93	0.6	99.2%		8.92	0.6	99.1%	9.49	0.3	105.4%
	24.01	0.1	100.0%		23.64	0.4	98.5%	25.28	0.1	105.3%
<i>Input Current</i>	0.219		η	0.349		η	0.26		η	
	13.14		78.227%		20.94	82.751%		15.6		
<i>+3.3V</i>	3.35	2	101.5%	3.35	2	101.5%	3.36	2	101.8%	
	9.46	0.3	105.1%		9.26	0.6	102.9%	9.23	0.6	102.6%
	23.72	0.4	98.8%		24.99	0.1	104.1%	24.48	0.4	102.0%
<i>Input Current</i>	0.396		η	0.306		η	0.442		η	
	23.76		80.076%		18.36	80.365%		26.52		



9.2 Regulation

9.2.1 LINE




Figure 6 – Line Regulation, Full Load



9.2.2 LOAD




Figure 7 – Load Regulation, 28 V and 60 VDC Input

10 Waveforms

10.1 Drain Voltage, Normal Operation



Figure 8 – 48 VDC, No Load.

Upper: I_{DRAIN} , 1 A/div

Lower: V_{DRAIN} , 50 V/div, 0.5 μ s / div




Figure 9 – 48 VDC Input, Full Load.

Upper: I_{DRAIN} , 1 A/div

Lower: V_{DRAIN} , 50 V/div, 0.5 μ s / div




Figure 10 – 48 VDC, Minimum Load.

Upper: I_{DRAIN} , 1 A/div

Lower: V_{DRAIN} , 50 V/div, 0.5 μ s / div




Figure 11 – 60 VDC Input, Full Load.

Upper: I_{DRAIN} , 1 A/div

Lower: V_{DRAIN} , 50 V/div, 0.5 μ s / div



10.2 Output Voltage Start-up Profile




Figure 12 – Start-up Profile, 48 VDC No Load
T: 10msec/div




Figure 13 – Start-up Profile, 48 VDC Full Load
T: 10msec/div

10.3 Load Transient Response (0.75 A to 2 A Load Step)

In the figures shown below, signal averaging was used to better enable viewing the load transient response. The oscilloscope was triggered using the load current step as a trigger source. Since the output switching and line frequency occur essentially at random with respect to the load transient, contributions to the output ripple from these sources will average out, leaving the contribution only from the load step response. +9 V and +24 V Loads were set to maximum.




Figure 14 – Transient Response
 Top: Load Current; 1 A/div.
 Bottom: +3.3 V Output
 100 mV, 1ms/div.



10.4 Output Ripple Measurements

10.4.1 Ripple Measurement Technique

For DC output ripple measurements, a modified oscilloscope test probe must be utilized in order to reduce spurious signals due to pickup. Details of the probe modification are provided in Figure 15 and Figure 16.

The 5125BA probe adapter is affixed with two capacitors tied in parallel across the probe tip. The capacitors include one (1) 0.1 μF /50 V ceramic type and one (1) 1.0 μF /50 V aluminum electrolytic. ***The aluminum electrolytic type capacitor is polarized, so proper polarity across DC outputs must be maintained (see below).***




Figure 15 – Oscilloscope Probe Prepared for Ripple Measurement. (End Cap and Ground Lead Removed)



Figure 16 – Oscilloscope Probe with Probe Master 5125BA BNC Adapter. (Modified with wires for probe ground for ripple measurement, and two parallel decoupling capacitors added)

10.4.2 Measurement Results at 48 VDC




Figure 17 – +3.3 V Ripple, Full Load, 20mV/div; T: 2usec/div

38mV p-p




Figure 18 – +9 V Ripple, Full Load, 50mV/div; T: 2usec/div

130mV p-p



Figure 19 – +24 V Ripple, Full Load, 50mV/div; T: 2usec/div

160mV p-p



11 Control Loop Measurements

11.1 Maximum Load




Figure 20 – Gain-Phase Plot, 28VDC Input Maximum Steady State Load
Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div.
Crossover Frequency = 4.55 kHz Phase Margin = 49.4°




Figure 21 – Gain-Phase Plot, 48VDC Input Maximum Steady State Load
Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div.
Crossover Frequency = 2.23 kHz Phase Margin = 63.7°






Figure 22 – Gain-Phase Plot, 60 VDC Input Maximum Steady State Load
Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div.
Crossover Frequency = 2.27 kHz Phase Margin = 76.7°

11.2 Minimum Load




Figure 23 – Gain-Phase Plot, 28 VDC Input Minimum Load
Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div.
Crossover Frequency = 4.97 kHz Phase Margin = 74.8°






Figure 24 – Gain-Phase Plot, 48 VDC Input Minimum Load

Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div.

Crossover Frequency = 1.28 kHz Phase Margin = 76.1°




Figure 25 – Gain-Phase Plot, 60 VDC Input Minimum Load

Vertical Scale: Gain = 8 dB/div, Phase = 40 °/div.

Crossover Frequency = 896Hz Phase Margin = 53.98°



12 Revision History

Date	Author	Revision	Description & changes	Reviewed
10-26-05	RSP	1.0	Initial release	VC, JC, KM



For the latest updates, visit our website: www.powerint.com

Power Integrations reserves the right to make changes to its products at any time to improve reliability or manufacturability. Power Integrations does not assume any liability arising from the use of any device or circuit described herein. POWER INTEGRATIONS MAKES NO WARRANTY HEREIN AND SPECIFICALLY DISCLAIMS ALL WARRANTIES INCLUDING, WITHOUT LIMITATION, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF THIRD PARTY RIGHTS.

PATENT INFORMATION

The products and applications illustrated herein (including transformer construction and circuits external to the products) may be covered by one or more U.S. and foreign patents, or potentially by pending U.S. and foreign patent applications assigned to Power Integrations. A complete list of Power Integrations' patents may be found at www.powerint.com. Power Integrations grants its customers a license under certain patent rights as set forth at <http://www.powerint.com/ip.htm>.

The PI Logo, **TOPSwitch**, **TinySwitch**, **LinkSwitch**, **DPA-Switch**, **EcoSmart**, **PI Expert** and **PI FACTS** are trademarks of Power Integrations, Inc. Other trademarks are property of their respective companies. ©Copyright 2005 Power Integrations, Inc.

Power Integrations Worldwide Sales Support Locations

WORLD HEADQUARTERS

5245 Hellyer Avenue
San Jose, CA 95138, USA.
Main: +1-408-414-9200
Customer Service:
Phone: +1-408-414-9665
Fax: +1-408-414-9765
e-mail: usasales@powerint.com

CHINA (SHANGHAI)

Rm 807-808A,
Pacheer Commercial Centre,
555 Nanjing Rd. West
Shanghai, P.R.C. 200041
Phone: +86-21-6215-5548
Fax: +86-21-6215-2468
e-mail: chinasonsales@powerint.com

CHINA (SHENZHEN)

Room 2206-2207, Block A,
Elec. Sci. Tech. Bldg.
2070 Shennan Zhong Rd.
Shenzhen, Guangdong,
China, 518031
Phone: +86-755-8379-3243
Fax: +86-755-8379-5828
e-mail: chinasonsales@powerint.com

GERMANY

Rueckertstrasse 3
D-80336, Munich
Germany
Phone: +49-89-5527-3910
Fax: +49-89-5527-3920
e-mail: eurosales@powerint.com

INDIA

261/A, Ground Floor
7th Main, 17th Cross,
Sadashivanagar
Bangalore, India 560080
Phone: +91-80-5113-8020
Fax: +91-80-5113-8023
e-mail: indiasales@powerint.com

ITALY

Via Vittorio Veneto 12
20091 Bresso MI
Italy
Phone: +39-028-928-6000
Fax: +39-028-928-6009
e-mail: eurosales@powerint.com

JAPAN

Keihin Tatemono 1st Bldg
2-12-20
Shin-Yokohama, Kohoku-ku,
Yokohama-shi, Kanagawa ken,
Japan 222-0033
Phone: +81-45-471-1021
Fax: +81-45-471-3717
e-mail:
japansales@powerint.com

KOREA

RM 602, 6FL
Korea City Air Terminal B/D,
159-6
Samsung-Dong, Kangnam-Gu,
Seoul, 135-728, Korea
Phone: +82-2-2016-6610
Fax: +82-2-2016-6630
e-mail:
koreasales@powerint.com

SINGAPORE

51 Newton Road,
#15-08/10 Goldhill Plaza,
Singapore, 308900
Phone: +65-6358-2160
Fax: +65-6358-2015
e-mail:
singaporesales@powerint.com

TAIWAN

5F, No. 318, Nei Hu Rd., Sec. 1
Nei Hu Dist.
Taipei, Taiwan 114, R.O.C.
Phone: +886-2-2659-4570
Fax: +886-2-2659-4550
e-mail:
taiwansales@powerint.com

EUROPE HQ

1st Floor, St. James's House
East Street, Farnham
Surrey, GU9 7TJ
United Kingdom
Phone: +44 (0) 1252-730-140
Fax: +44 (0) 1252-727-689
e-mail: eurosales@powerint.com

APPLICATIONS HOTLINE

World Wide +1-408-414-9660

APPLICATIONS FAX

World Wide +1-408-414-9760

